

M12 Field Assembly Connector, Screw Termination, Straight





CE RoHS







CE RoHS

Specification

Number of positions	2	3	4	4D	5	5B
Insert arrangement (Female)						
Insert arrangement (Male)						
Rated current	4A					
Rated voltage	250V				60V	
Wire gauge	22AWG/0.34mm²					


Number of positions	6	8
Insert arrangement (Female)		
Insert arrangement (Male)		
Rated current	2A	
Rated voltage	30V	
Wire gauge	24AWG/0.25mm²	
Insulation resistance	≥100MΩ	
Contact resistance	≤5mΩ	
Temperature range	-25℃ ~ +80℃	
Protection rating	IP67(Mated)	
Body material	PA66	
Screw nut material	Brass, Nickel Plated	
Insulation material	PA66+GF	
Contact termination	Screw Termination	
Contact material	Brass, Gold Plated	
Seal	NBR, Black	
Shielding	Unshielded	
Mating cycles	≥500	

Part Number

Number of positions	Female	Male
2	RHT-634-3371-02-PG7/PG9	RHT-634-3370-02-PG7/PG9
3	RHT-634-3371-03-PG7/PG9	RHT-634-3370-03-PG7/PG9
4	RHT-634-3371-04-PG7/PG9	RHT-634-3370-04-PG7/PG9
4D	RHT-634-3371-4D-PG7/PG9	RHT-634-3370-4D-PG7/PG9
5	RHT-634-3371-05-PG7/PG9	RHT-634-3370-05-PG7/PG9
5B	RHT-634-3371-5B-PG7/PG9	RHT-634-3370-5B-PG7/PG9
6	RHT-634-3371-06-PG7/PG9	RHT-634-3370-06-PG7/PG9
8	RHT-634-3371-08-PG7/PG9	RHT-634-3370-08-PG7/PG9


M12 Field Assembly Connector, Solder Cup, Straight





CE RoHS





CE RoHS

Specification

Number of positions	2	3	4	4D	5	5B
Insert arrangement (Female)						
Insert arrangement (Male)						
Rated current	4A					
Rated voltage	250V				60V	
Wire gauge	22AWG/0.34mm²					

Number of positions	6	8	12	17
Insert arrangement (Female)				
Insert arrangement (Male)				
Rated current	2A		1.5A	
Rated voltage	30V			
Wire gauge	24AWG/0.25mm²		26AWG/0.14mm²	
Insulation resistance	≥100MΩ			
Contact resistance	≤5mΩ			
Temperature range	-25℃ ~ +80℃			
Protection rating	IP67(Mated)			
Body material	PA66			
Screw nut material	Brass, Nickel Plated			
Insulation material	PA66+GF			
Contact termination	Solder Cup			
Contact material	Brass, Gold Plated			
Seal	NBR, Black			
Shielding	Unshielded			
Mating cycles	≥500			

Part Number

Number of positions	Female	Male
2	RHT-634-3223-02	RHT-634-3091-02
3	RHT-634-3223-03	RHT-634-3091-03
4	RHT-634-3223-04	RHT-634-3091-04
4D	RHT-634-3223-4D	RHT-634-3091-4D
5	RHT-634-3223-05	RHT-634-3091-05
5B	RHT-634-3223-5B	RHT-634-3091-5B
6	RHT-634-3223-06	RHT-634-3091-06
8	RHT-634-3223-08	RHT-634-3091-08
12	RHT-634-3223-12	RHT-634-3091-12
17	RHT-634-3223-17	RHT-634-3091-17